

EMI Conductive Copper Foil Tape Heat Resistant For Slugs

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: Jinshunlai
- Certification: IOS
- Model Number: 0.1mm-900mm
- Minimum Order Quantity: 1kg
- Price: 5000usd
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union,D/P
- Supply Ability: 90000ton



Product Specification

- Adhesive: Acrylic
- Adhesive Strength: High
- Application: Electrical, Insulation, Shielding
- Tensile Strength: High
- Thickness: 0.06mm
- Width: 50mm
- Color: Red Yellow
- Highlight: **Heat Resistant Copper Foil Tape,
Slugs Copper Foil Tape,
EMI conductive copper foil**

for more products please visit us on copper-solid.com

Product Description

Key attributes

Industry-specific attributes

Adhesive	Acrylic
Adhesive Side	Single Sided
Design Printing	No printing
Material	Cooper Foil
Feature	Heat-Resistant
Use	MASKING

Other attributes

Place of Origin	China
Brand Name	jinshunlai
Model Number	Xinst0701
Feature	Strong Adhesive
Color	Customized
Adhesive Side	Single
Application	Electronic Products
Length	Custom Length

Packaging & delivery

Package Type:	Export standard packing for Copper Foil Tape.(If customers have special requirements, we also can make accordingly.) <input type="checkbox"/> <input type="checkbox"/>
---------------	--

Supply Ability

Supply Ability	10000 Roll/Rolls per Day
<h3>Product details</h3> <h2>Copper Foil Tape</h2> <p>-Copper Electrical Adhesive Tape is as a smooth copper (purity is 99.95%) foil backing with a acrylic pressure-sensitive adhesive and liner.</p>	

-It is have conductive or not conductive adhesive.

-The unplated copper with conductive adhesive is a common EMI shielding tape for non-corrosive conditions.

Features

.excellent heat- exchanging

performance

.high softening temperature and high
electric conductivity

.chemical resistance

.EMI RFI Shielding Barrier

Properties

Item	Copper Foil Tape
Size	5mm*20m, 10mm*20m, 20mm*20m or customized
Material	Copper Foil + Acrylic
Purity of Coper foil	99.99%
Shielding Effectiveness	80-115db
Holding Power	48hours
Feature	(1) Good electrical conductivity, its made of 99.99% Copper. (2) Heat-Resistant, From -10 to 120 . (3) Eliminate electromagnetic interference/EMI Shielding. (4) Radiation protection (5) Easy to tear, no adhesive residue, for a wide range.
Application	EMI Shielding, Slug repellent, Paper Circuits, Electrical Repairs, Grounding, Arts ,Crafting and Snail prevention etc.
Lead Period	1-7days



Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China