

1/16" 1/2" Stainless Steel Strip Coil 310 316 304 410 430 OEM

Basic Information

Place of Origin: china Brand Name: jinshunlai

• Certification: ISO, AISI, ASTM, GB, EN, DIN

Model Number: 0.1mm-900mm

• Minimum Order Quantity: 1kg

Price: Contact Us

Packaging Details: Waterproof Paper, Steel Strip Packed and

other Standard Export Seaworthy Package,

or customized package

• Delivery Time: 5day

• Payment Terms: L/C, T/T, Western Union

• Supply Ability: 90000ton



Product Specification

• Application: Construction, Decoration, Industry,

Machinery, Etc

Edge: Slit Edge, Mill Edge
Grade: 200/300/400 Series
Length: 1000-6000mm
Material: Stainless Steel

Packaging: Standard Export Packing Or As Customer's

Request

Standard: ASTM, AISI, DIN, EN, GB, JIS
Surface: 2B, BA, HL, No.1, No.4, 8K
Technique: Cold Rolled, Hot Rolled

Thickness: 0.1-20mm
 Tolerance: ±0.02mm
 Width: 1000-2000mm

Highlight: 430 stainless steel strip coil,

1/2" stainless steel strip coil,



More Images



Product Description

PRODUCT DESCRIPTION

410 430 Cold Rolled Stainless Steel Strip for Washing Machine Inner Bucket

430 stainless steel is a general steel with good corrosion resistance. Its thermal conductivity is better than austenite, its thermal expansion coefficient is smaller than austenite, its heat resistance fatigue, and the addition of stabilized element titanium has good mechanical properties at the welding seam.

430 stainless steel for building decoration, fuel burner parts, household appliances, home appliances parts.

Product Description

Stainless steel does not stain, corrode, or rust as easily as regular carbon steel and provides high strength and impact resistance along with the aesthetic appeal. The material also has anti-bacterial qualities and is easy to clean and sanitize. **Stainless steel sheet** and **stainless steel plate** are both a perfect solution for applications that require a durable metal with anti-oxidation qualities.

We offer **Stainless steel sheet** and **stainless steel plate** with high quality and competitive price. And the material is manufactured by TISCO, BAOSTEEL, POSCO, LISCO and so on. Mainly used in architectural decoration, luxury doors, elevator decoration, metal tank shell, shipbuilding, train interior decoration, and outdoor engineering, advertising nameplates, ceilings and cabinets, aisle panels, screens, tunnel projects, hotels, guesthouses, entertainment venues, kitchens Equipment, light industry, etc.


Standard:	JIS, AiSi, ASTM, GB, DIN, EN, JIS, AISI, ASTM, GB, DIN, EN, etc.	Place of Origin:	Jiangsu, China		
Brand Name:	ZLYS	Model Number:	201 304		
Type:	Welded	Steel Grade:	300 Series		
Application:	Industry/Construction	Certificat ion:	ISO, AISI, ASTM, GB, EN, DIN, JIS		
Welding Line Type:	ERW	Toleranc e:	±1%		
Processing Service:	Welding	Grade:	SS 304 SS316I		
Product name:	Stainless Steel Sheet	Key Word:	Schedule 10 Stainless Steel Sheet		
Surface:	Polished	Price Term:	CIF CFR FOB EX- WORK		
MOQ:	1 Ton	Techniq ue:	Hot Rolled , Cold Rolled , Extrusion		
Payment:	L/C,T/T	Edge:	Mill Edge Slit Edge		
Port:	Qingdao, China				


Specification

ITEM	DESCRIPTION
Product Name	ss coil supplier hot roll coil price 430BA 304BA 201 stainless steel coil
Standard	JIS, AISI, ASTM, GB, DIN, EN, etc.
Certificatio n	ISO, BV, SGS
Material	200 series 300 series 400 series 600 series
Model Number	304,304L,316L,316Ti,309S,310S,321,321H314,2205,S32205,,2507, S32750,600,631800H,825901,903,904L,N08904,,1.4529,N08926,317L, 317LN347H,348H(253MA,S30815),254SMO,S31254,25- 6MOS32760440A, 440B,440CGH3030GH3039(C276,HC-276 Hastelloy)724L,725LN
Width	100mm, 500mm, 600mm, 1000mm, 1250mm, 1500mm, 1800mm, 2000mm, or, as required
Thickness	0.2mm-15mm, or as required
Technique	Cold Rolled, hot rolled
Surface Treatment	Polishing, Annealing, Pickling, Bright, or as required
Surface Finished	BA/2B/NO.1/NO.3/NO.4/8K/HL/2D/1D, or as required
Thickness Tolerance	±0.05mm, or as required
Package	Standard export seaworthy package . Water proof paper+Metal pallet+Angle bar protection+Steel belt or as required.
Payment	$\mbox{L/C}$ at sight or 30% TT as deposit and the balance paid against copy of B/L, west union, money gram
Price Term	CIF, CFR, FOB, EX-WORK
Loading Port	Shanghai, Lianyungang, Tianjin, Ningbo,China
Place of Origin	Jiangsu, China
Delivery Time	Prompt delivery 7-15 days after deposit or as order quantity.
MOQ	1 ton , sample or trial order acceptable
Sample	free provided, courier fee by the buyer's side.
Advantage s	Showing the splendor of your quality, wear-resistant as well, strong corrosion resistance and decorative effect.
Application	Stainless coil is commonly used in kitchen equipment, furnace parts, heat exchangers and decorative applications, etc
Container Size	20ft GP: 5898mm(Length)x2352mm(Width)x2393mm(High) 40ft GP: 12032mm(Length)x2352mm(Width)x2393mm(High) 40ft HC: 12032mm(Lengh)x2352mm(Width)x2698mm(High)













Product Display

1 Todaot Biopiay							
Surf ace finis h	Defination	Application					
2B	Those finish,after cold rolling, by heat treatment or other equivialent treatment and lastly by cold rolling to given appropriate luster	Medical equipment, food industry, construction material, kitchen utensils					
ВА	Medical equipment, food industry, construction material, kitchen utensils	Kitchen utensils, electric equipment, buliding construction					
N0.4	Those finished by polishing with NO.180 abrvsivea specified in JIN R6001	Kitchen utensils, buliding construction, medical equipement					
HL	Those finished polishing so as to give continuous polishing streaks by using abrasive of suitable grain size	Buliding construction					
8K	A mirror like reflective surface by polidhing with finer abrasivea over 800 mesh	Reflector, mirror, interor- exterior decoration					

Stainless Steel Composition Chart, Percentage (%)

Gra de	C, ≤	Mn, ≤	P, ≤	S, ≤	Si , ≤	Cr	Ni	Мо	Ν, ≤
304	0.08	2	0. 04 5	0. 03	1	18.0- 20.0	8.0- 11.0	-	-
304 L	0.03	2	0. 04 5	0. 03	1	18.0- 20.0	8.0- 11.0	-	-
316	0.08	2	0. 04 5	0. 03	1	16.0- 18.0	10.0- 14.0	2.00- 3.00	-
316 L	0.03	2	0. 04 5	0. 03	1	16.0- 18.0	10.0- 14.0	2.00- 3.00	-
321	0.08	2	0. 04 5	0. 03	1	17.0- 19.0	9.0- 12.0	-	0.1
201	0.15	5.50- 7.50	0. 06	0. 03	1	16.0- 18.0	3.5- 5.5	-	0.25
301	0.15	2	0. 04 5	0. 03	1	16.0- 18.0	6.0- 8.0	-	0.1
302	0.15	2	0. 04 5	0. 03	0. 7 5	17.0- 19.0	8.0- 10.0	-	0.1
303	0.15	2	0. 2	≥0 .1 5	1	17.0- 19.0	8.0- 10.0	-	-
305	0.12	2	0. 04 5	0. 03	1	17.0- 19.0	11.0- 13.0	-	-
308	0.08	2	0. 04 5	0. 03	1	19.0- 21.0	10.0- 12.0	-	-
309 S	0.08	2	0. 04 5	0. 03	1	22.0- 24.0	12.0- 15.0	-	-
310 S	0.08	2	0. 04 5	0. 03	1. 5	24.0- 26.0	19.0- 22.0	-	-
310 H	0.04- 0.10	2	0. 04 5	0. 03	0. 7 5	24.0- 26.0	19.0- 22.0	-	-
316 Ti	0.08	2	0. 04 5	0. 03	1	16.0- 18.0	10.0- 14.0	2.00- 3.00	0.1
317 L	0.03	2	0. 04 5	0. 03	0. 7 5	18.0- 20.0	11.0- 15.0	3.0- 4.0	0.1
321 H	0.04- 0.10	2	0. 04 5	0. 03	0. 7 5	17.0- 19.0	9.0- 12.0	-	-
347 H	0.04- 0.10	2	0. 04 5	0. 03	0. 7 5	17.0- 19.0	9.0- 13.0	-	-
348 H	0.04- 0.10	2	0. 04 5	0. 03	0. 7 5	17.0- 19.0	9.0- 13.0	-	-
220 5	0.03	2	0. 03	0. 02	1	22.0- 23.0	4.5- 6.5	3.0- 3.5	0.14- 0.20
250 7	0.03	1.2	0. 03	0. 02	0. 8	24.0- 26.0	6.0- 8.0	3.0- 5.0	0.24- 0.32

			5		_				
410	0.08- 0.15	1	0. 04	0. 03	1	11.5- 13.5	-	-	-
420	0.15, ≥	1	0. 04	0. 03	1	12.0- 14.0	-	-	-
430	0.12	1	0. 04	0. 03	1	16.0- 18.0	-	-	-
440 A	0.60- 0.75	1	0. 04	0. 03	1	16.0- 18.0	-	≤0.75	-
440 B	0.75- 0.95	1	0. 04	0. 03	1	16.0- 18.0	-	≤0.75	-
440 C	0.95- 1.20	1	0. 04	0. 03	1	16.0- 18.0	-	≤0.75	-
440 F	0.95- 1.20	1.25	0. 06	0. 15	1	16.0- 18.0	0.5	-	-
800 H	0.05- 0.10	1.5	0. 04 5	0. 01 5	1	19.0- 23.0	30.0- 35.0	-	-
904 L	0.02	2	0. 04 5	0. 03 5	1	19.0- 23.0	23.0- 28.0	4.00- 5.00	0.1
15-5 PH	0.07	1	0. 04	0. 03	1	14.0- 15.5	3.5- 5.5	-	-
17-4 PH	0.07	1	0. 04	0. 03	1	15.5- 17.5	3.0- 5.0	-	-
17-7 PH	0.09	1	0. 04	0. 04	1	16.0- 18.0	6.5- 7.75	-	-



Copper Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China